


Pipe Jacking/Microtunnelling

Dr. Mark Knight

Centre for Advancement of Trenchless Technologies (CATT)
University of Waterloo

1

New Installations



2

Pipe Jacking

- Oldest method of trenchless technology
- Applications
 - Larger Diameter Pipe (1050 mm and up)
- Lengths can range from 3 to over 200m




3

Pipe Jacking

- Person entry
 - Pipe diameters greater than 900 mm (36")
 - Difficult to work in excavations of this size
 - Practically limited to dia. greater than or equal to 1075 mm (42")
- Pipe installation process occurs from entrance and exit shaft
 - Access way locations

4

Pipe Jacking Process



Pipe Jacking

- Material excavation completed by persons within the excavation
 - Manual or machine face excavation
- Excavation takes place in front of an articulated shield
 - Designed for worker safety
 - Maintains open bore for pipe jacking or tunnel lining construction
 - Shield guided with individually controlled hydraulic jacks

Pipe Jacking Excavation



7

Pipe Jacking Excavation



8



Pipe Jacking

- Types of Tunneling
 - Hand mining
 - Liner Plate
 - Jack Reinforced Concrete Pipe
 - Jack Steel Liner
 - Cap and Leg (Wood Lined Tunnel)

9





Pipe Jacking Process

- Simple cyclic procedure
- Utilizes thrust from hydraulic jacks to force the pipe forward
 - Pipe placed on cradle in the entry or jacking pit
 - Thrust developed from thrust blocks
 - Concrete, steel, soil excavation


10

Pipe Jacking Pit



11

Pipe Jacking Pit



12

Pipe Jacking Process

Unstable soil


- Face excavated simultaneously with the jacking operation
 - Minimize over excavation and the risk of face collapse
- After pipe jacked into place hydraulic rams are retracted and another pipe length is installed

13

Pipe Jacking Process

Stable soil

- Face excavation may precede the jacking operation
- All spoils removed through the inside of the pipe to the jacking pit




14

Hand Excavation



15

Pipe Jacking Process





Pipe Jacking Pit

- Jacking pit size is function of:
 - Length of pipe segments
 - Pipe diameter
 - Shield dimensions
 - Thrust wall design
 - Jack size
 - Pressure rings
 - Guide rail systems

17



Pipe Jacking Pit

- Pit should be shored
 - Timber, steel piling or shaft liner plate, ground freezing
- For projects requiring large thrust
 - Design of launch pit is critical
- Pit should be dry
- Floor preparation key for controlling alignment

18



Pipe Jacking Pit

- For a large job the placement of a concrete mud slab on the shaft floor is recommended
- For a smaller job the placement of a 300mm of crushed stone is recommended

19



Pipe Jacking Force

- Force on jacked pipe includes:
 - Pipe dead weight
 - Penetration resistance
 - Soil-pipe friction
- Jacking force applied by two, four or six jacks

20



Other Forces

- Soil dead load
- Railway or highway live loads
- Jacking force must not exceed allowable pipe compressive strength
 - Critical design location is the joints
 - Low surface area - high stress
 - Water tightness??

21



Pipe Jacking Force

Soil-pipe frictional force minimized by the application of lubricant to the outer pipe surface

- Can reduce jacking force by 50%
- Manual application or pumping of bentonite slurry around pipe
- Polymers
 - Advantage only small amount required

22



Pipe Jacking Force

To minimize pipe damage during jacking

- Packing material can be placed between the pipe joints
 - 12 to 19mm plywood
 - 12 to 25mm manila rope, jute, oakum
- Provides joint cushioning and flexibility


23



Pipe Jacking Force


For long pipe installations

- Intermediate jacking stations may be used
- Set of hydraulic jacks placed between pipe segments



24

Intermediate Jacking Station (IJS)



25

Intermediate Jacking Station (IJS)



26



Intermediate Jacking Station (IJS)

- Total drive expected to exceed capacity of main jacks
- Capacity 100 to 1600 tons
- Diameter around 36" length 56"
- IJS assembled in four segments
- IJS must match pipe dia. for proper operation

27



Intermediate Pipe Jacking

Three step pipe jacking process:

1. Intermediate jacks are used to jack the forward sections of pipe
 - Thrust is provide by the pipe section behind the intermediate jacks
2. Intermediate jacks are retracted
3. Back section of pipe is jacked using the launching pit cradle

28

Jacking Pipe



CLAY PIPE

**REINFORCED
CONCRETE PIPE**




29

Jacking Pipe Material

- Reinforced concrete (RCP)
- Polymer concrete
- Fibreglass (Hobas)
- Vitrified clay (VCP)
- Steel
- Ductile Iron
- Composites

30



31



32



Pipe Joints

- Must withstand high jacking forces
- Create water tight seals
- Flush joints to decrease jacking forces

33



PJ Applications

- Sewers, and drainage construction
- Gas and watermain
- Oil pipelines
- Industrial pipelines
- Telecommunication
- Pedestrian subways (access tunnels)

34

PJ Advantages

- Quick set-up
- When grade is critical
- Versatile in various ground conditions
- Cost efficient for large diameter pipe
- Small surface settlements
 - Settlement controlled by face excavation



35

PJ Limitations

- Access to the face of the tunnel is needed at all times
- Speed of the mining operation is reliant on:
 - Speed of labour (workers)
 - Soil Matrix
 - Rock
 - Soft Soil
 - Water Table
- Dewatering of tunnel path is usually required



36



New Installation


Steering Methods

- Microtunnelling
- Horizontal directional drilling (HDD)

37



Microtunnelling




38

Microtunnelling

- Remotely controlled and guided pipe jacking technique that provides support to the excavation face and does not require personnel entry into the tunnel
- Laser guided micro TBM used for soil excavation
- Drive from access way to access way (manhole locations)
- Mainly used for gravity sewers but can be used for large water mains

39

Microtunnelling



- Non-person entry
- Machine excavated (mini TBM)
- Remote controlled
- Similar to pipe jacking
- Pipe OD less than 1.0m

40

Tunnel Boring (TBM)



people

World largest tunneling machine
(14.2 m in diameter)

Chunnel




41

Microtunnelling



42



Microtunnelling

- Accuracy typically better than ± 25 mm per drive
- Laser controlled
- Variety of machines for different soil conditions
- Main applications: deep systems

44



Microtunnelling

- Accurate monitoring and adjusting of the alignment and grade as work proceeds
 - Pipe can be installed on precise line and grade
- Generally used for pipe diameters less than 900mm (36 inches)
- Can be used for larger diameters

45



Launching and Exit Pits

- Use same design procedure as for pipe jacking
- Length of tunneling machine can control launch and exit pit size

46

Entrance and Exit Pit Shields

- Neoprene sheet stock held in steel ring




47

Entrance and Exit Pit Shields

- Prevents slurry and ground water from entering into shafts

48

Jacking System



49

History

- Originated in Japan and Germany in 1970's
- Development government sponsored
 - Need for pipe construction method with minimum surface disruption in over congested areas
 - Komatsu introduced first Microtunnelling machine in 1975 - IRONMOLE
 - ISEKI inc introduced there machine in 1976
 - Ability to counter balance earth pressure mechanically and hydraulically

50



History

First Microtunnelling project in North America

- Fort Lauderdale Florida in 1984
 - 615 feet of 72 inch pipe under I-95
- Second project
 - Bridgeport CT in 1986
 - 3610 feet of 72 inch pipe

51



History

As of October 1996

- Total MT North America footage 547,100 feet
- Total number of projects = 254

52



MT Classification Methods

- Based on mode of operation
 - Slurry method
 - Auger method

53




Slurry Method

- Tunnel face is supported mechanically or by a pressurized slurry
- Spoils (cuttings) removed hydraulically in the form of a slurry
- Conveying fluid is used to counteract hydrostatic forces caused by ground water pressure and soil removal

54


Slurry Method

LOVAT MTS 1000



55

Slurry Method




56

Slurry Method

- Soil cut mechanically
 - Cutting head designs depends of soil or rock type
- Cuttings removed by hydraulic action
- Cuttings enter bore head through inlet openings and placed in suspension in the slurry chamber - water and bentonite

57

Slurry Method



58



Lubrication System

Typical system components:

- Variable speed discharge pump
- Charge pump
- Intermediate pumps
- Flow meter
- Flow controller
- Pit by pass to permit diversion of flows
- Piping, flexible hoses and cabling

59



Slurry Separation

Typical separation plant components:

- Vibrating screens
- Cyclones for small particle separation
- Clay ball separator
- Settlement tank

60



Slurry System

- Depth of ground water up to 30m can be managed
- Due to efficiency of shield small pipes can be used
- Full measurement and control of slurry flows

61




Auger Method

- Soil cutting at the face by a bore head and soil removal by means of a continuous flight of augers
- Augers run in a separate guiding pipe
- Better suited for cohesive soils

62


Auger Method



63

Auger Method

LOVAT MTS 1000




64

Auger Method (Drill)

Phase I

- a steerable pilot tube is jacked into the ground displacing the soil.



65

Steerable pilot tube




66

Phase I



67

Guidance System



68

Phase I




69

Auger Method (Drill)

Phase II

- install a temporary steel casing



70


Standard Reaming Heads



71

Phase II

Full Face Cut with Ground Water Seal



72


Standard Reaming Heads



73

Phase II

RVS 80 Reaming Head with Ground Water Seal



74

Full face with Ground water control



75

Phase II – Casing with Augers



76

Phase II – Casing Installation




77

Auger Method (Drill)

Phase III

- the product pipe is installed




78

Auger Method (Drill)

Phase III

- the product pipe is installed



79

Phase III



80



Auger Method (Drill)

- Steered pilot tube
- Combined Phase II & III (<150mm OD)
- Phase III (150 to 225mm)
- Shafts 2m dia
- Drive lengths 60m plus

81




MT Equipment Selection

- Variety of machine types
- Choice depends on ground condition
 - Type of soil/rock
 - Sand, gravel, clay, boulders, etc
 - Ground water table
- Project success depends on have a proper soil investigation

82

MT Equipment



83

MT Advantages

- Grade and alignment accuracy (± 25 mm)
- Works well in a wide variety of soil conditions
 - Some problems with boulders
- Works well below groundwater table
 - No expensive dewatering systems required
 - Up to approx 30m below GWT
- Increasing line depths does not significantly increase cost

84



MT Advantages

- Worker safety
- No ground surface settlement

85



MT Disadvantages

- High equipment capital cost
- Lateral connections?
- Difficulty with boulders
- Changing ground conditions
- Wood and debris

86



Microtunnelling Pipe

- Same as for pipe jacking

87



Other Recommendations

- Ensure sufficient room adjacent to the launch pit for:
 - Pipe and machine storage
 - Drill fluid mixing and recycling
 - Spoil/cutting removal

88



Safety Precautions

- Safe pit design
- Overhead clearance for equipment
 - Lower pipe and machine into the access launch pits
 - Retrieve machine from exit pits
- Underground utility clearance

89



MT Risks

- Pipe diameter
 - Risk decreases as diameter increases
- Length
 - Risks increases as length increases

90

Cost

- 36" (900 mm) = \$650 to 850/ft
- 48" (1200 mm) = \$800 to 1200/ft
- Shafts
 - 50 to 100k
 - Depends on groundwater, depth & soil conditions
- Need over 1million dollar project to start to look at Microtunnelling

91

Microtunnelling in KL



92

Microtunnelling in KL

- Approx. 70km 1800mm OD sewer
- LOVAT MTS (Toronto Canada)
- 3 to 4 pipe sections 2950mm long per day
- Drive length 64 sections (~190m long)
- ~RM90,000,000 Project

93

Microtunnelling in KL



94



Microtunnelling in KL

- MT machine currently stuck under the river
- Will sink rescue shaft to recover